

# POWER SUPPLY CONSOLE

## Mod. 1500-A/EV



A set of power supplies is mounted on the console mod. 1500-A/EV with professional characteristics and general use; DC and AC voltages are available, which are fixed and variable, protected against overloads and short-circuits.

The console can be mechanically locked to the table mod. TOP/EV (or to any laboratory table).

On the rear side of the console, there are 4 sockets to connect any instrument which can be laid on the upper part covered with a rubber carpet.

### TECHNICAL SPECIFICATIONS:

- DC power supplies
  - Output 1: + 5Vdc, 2A;
  - Output 2: +12Vdc 2A, -12Vdc 1A.

Stabilized voltages electronically protected against short-circuits and overloads.

- Output 3: 0 ÷ 30 Vdc / 0 ÷ 2A.

Voltage and current adjustable with multi-rev potentiometer for the voltage, one rev. for the current.

- AC power supply
  - Output 4: 2x0 ÷ 24Vac - 4A (insulated);
  - Output 5: 0 ÷ 250 Vac - 1A (not insulated) T.M.C.B..

General magneto-differential power supply switch

**Power supply:** 230 Vac 50 Hz single-phase - 500 VA  
(Other voltage and frequency under request)

**Dimensions:** 1000 x 340 x 185 mm

**Weight:** 30 kg

**Table TOP/EV dimensions:** 2000 x 1000 x 860 mm